

Fertilizer 5-0-31



Turf Products

FEATURES & USE TIPS:

- 20% nitrogen derived from NS-54™ polymer coated sulfur coated urea
- Provides iron for improved turf color.
- SGN 215 for fairways, roughs and other turf areas.

PRODUCT SPECIFICATIONS:

N (5%): Urea Nitrogen*
*1.00% Slowly available nitrogen from polymer coated sulfur coated urea

K - as (K₂O) (31%): Potassium Chloride

Fe (10%): Iron

Cl (26.18%): Chlorine

Following is a specimen label that may at some point be revised or otherwise become out of date. It is intended as a guide in providing general information regarding the use of this product. Always read and follow the label on the product container.

PRODUCT CODE:

APT5151

Date: 051810
Supersedes: 000000
Label: C10

PRODUCT CHARACTERISTICS:

Product Type:
Fertilizer

Nitrogen Type:
NS-54

Particle Size:
SGN: 215

Net Weight:
50 lbs.

Coverage:
20,000 sq. ft @
Medium Rate

Bags / Pallet:
45

The Andersons logo is a registered trademark of The Andersons, Inc.; NS-54 is a trademark of The Andersons, Inc.

To order, contact your local Andersons Golf Products distributor.

*For more information, contact Andersons at our website:
www.andersonsgolfproducts.com
or call 1-800-225-2639.*



Turf Products

Fertilizer

5-0-31

- Contains NS-54™ slow release nitrogen to provide uniform growth with extended nitrogen feeding
- Provides iron for improved turf color.
- SGN 215 for fairways, roughs and other turf areas.

GUARANTEED ANALYSIS

Total Nitrogen (N)	5.00%
5.00% Urea Nitrogen*	31.00%
Soluble Potash (K ₂ O)	10.00%
Iron (Fe)	26.18%

Plant nutrients derived from urea, potassium chloride, polymer coated sulfur coated urea and ferric oxide.

*1.00% Slowly available nitrogen from polymer coated sulfur coated urea.

F292

Information regarding the contents and levels of metals in this product is available on the internet at <http://www.regulatory-info-ap.com>

GENERAL INFORMATION

The Andersons Turf Products 5-0-31 provides grass with nitrogen and potash for maintaining strong, vigorous turf.

The nitrogen in this product is both readily and slowly available which makes this product excellent for applications throughout the growing season when the minimum soil temperatures are greater than 55°F to 60°F and not exceeding 85°F.

This product is dust free and free flowing. The uniform particle sizing assures easy and accurate applications.

DIRECTIONS FOR USE

Apply only as directed. Apply during the growing season.

Application Rates:

LOW:	2.00 lbs./1,000 sq. ft.
MEDIUM:	2.50 lbs./1,000 sq. ft.
HIGH:	3.00 lbs./1,000 sq. ft.

FLORIDA APPLICATIONS: We recommend that you follow the Florida Green Industries BMP's at http://www.flaes.org/pdf/BMP_Book_final.pdf

FLORIDA APPLICATIONS: We recommend that you follow the Florida Golf Course BMP's at <http://www.flaes.org/pdf/gfcbmp07.pdf>

For all applications:

- Apply to dry foliage.
- Water in after application with a minimum of 0.2 inches to help move particles into the turf canopy.
- Do not collect clippings for at least one mowing following application to avoid particle pick-up.
- Apply at the LOW RATE when temperatures exceed 85°F.

Notice: This product contains the micronutrient iron for extra greening and to help prevent iron deficiency. Iron may stain concrete and other surfaces. Misapplied product to these surfaces should be removed promptly by sweeping or blowing. Do not wash off with water.

Recent research has shown that well-maintained turf is an effective environmental buffer that prevents pollutants from entering our natural water bodies. To help protect these natural resources, avoid applying product to sidewalks, driveways, roadways, and other impervious surfaces. Sweep any misplaced granules back onto the area you are treating immediately after application, since storm drains often empty directly to nearby waterways.

STORAGE AND USE

Store in a clean, dry place. Reseal opened bag by folding top down and securing. Use only in clean, dry spreaders. Do not leave unused product in spreaders.

IMPORTANT: READ BEFORE USE:

Read the entire Directions for Use and the Warranty Disclaimer and Limitation of Liability before using this product. If terms are not acceptable, return the unopened product container at once. By using this product, user or Buyer accepts the following Warranty Disclaimer and Limitation of Liability:

WARRANTY DISCLAIMER and LIMITATION of LIABILITY:

Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions. Manufacturer makes NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. To the extent consistent with applicable law, it is Manufacturer's intent to LIMIT ANY LIABILITY FOR SPECIAL, CONSEQUENTIAL OR INCIDENTAL ECONOMIC DAMAGES to refund of purchase price or replacement of product, at Buyer's choice. To the extent consistent with applicable law, Manufacturer DISCLAIMS ANY LIABILITY FOR COMPENSATORY OR OTHER DAMAGES ARISING OUT OF ANY USE CONTRARY TO LABEL DIRECTIONS. Use contrary to label directions is not permitted.

LEGAL RIGHTS:

THIS LIMITED WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS; YOU MAY HAVE OTHER RIGHTS THAT VARY FROM STATE/ JURISDICTION TO STATE/JURISDICTION.

Product of U.S.A.

Manufactured by:
The Andersons Lawn Fertilizer Division, Inc.
P.O. Box 119
Maumee, OH 43537
www.andersonslawnproducts.com

The Andersons logo is a registered trademark of The Andersons, Inc.; NS-54 is a trademark of The Andersons, Inc.


Suggested Spreader Settings

These suggested spreader settings are not intended to replace calibration. Please calibrate your spreader before applying product.

50 lbs. feeds 25,000 sq. ft. (0.57 acre) with 0.62 lbs. K₂O/1,000 sq. ft. at the LOW RATE
50 lbs. feeds 20,000 sq. ft. (0.46 acre) with 0.77 lbs. K₂O/1,000 sq. ft. at the MEDIUM RATE
50 lbs. feeds 16,600 sq. ft. (0.38 acre) with 0.93 lbs. K₂O/1,000 sq. ft. at the HIGH RATE

SPREADER	GROUND SPEED	WIDTH OF COVERAGE	LOW RATE 2.00 lbs/1,000 sq. ft.	MEDIUM RATE 2.50 lbs/1,000 sq. ft.	HIGH RATE 3.00 lbs/1,000 sq. ft.
Andersons Accupro 2000, SR-2000 (cone 5)	3 mph	10 feet	H 1/4	1 3/4	J 1/4
Scotts R8, R-8A (cone 5)	3 mph	10 feet	G	H	I
Lely Models WTR, WFR, HR, 1250 (PTO at 450 rpm) Pattern III-C	4.5 mph	28 feet	3	4	4 1/4
Vicon 03 Series	4.5 mph	28 feet	16	18 1/4	20 1/2

SGN 215
Net Wt. 50 Lbs. (22.68 kg)



0 31865 31047 8

APT5151

C10 (APTBLKPMGRNB)