



SLICKY STICKY®

LOWER COSTS - BETTER RESULTS

Slicky Sticky® is a soil amendment that helps control soil erosion. It promotes water penetration into the soil, which reduces water run-off. It also flocculates suspended soil particles minimizing soil loss.

Slicky Sticky® makes any mulch slurry slippery which helps reduce or eliminate clogging. Also, more mulch can be used per tank load. More mulch per tank load increases productivity.

Slicky Sticky® helps capture more soil moisture which results in improved seed germination.

Slicky Sticky® reduces costs and improves productivity. Less erosion means fewer call backs. Fewer clogs means less down time. More mulch per tank load results in greater coverage per load.

Slicky Sticky® is environmentally safe, E.P.A. exempt, and totally biodegradable in 3 to 6 months.

Mixing Instructions: Use is 2-8 ounces per 100 gallons of slurry. Slowly add to the slurry during agitation. Allow to mix at least five minutes. **NEVER MIX MORE THAN 8 OUNCES PER 100 GALLONS OF WATER.**

APPLICATION RATES VARY FROM 3-20 POUNDS PER ACRE: Soil erosion is caused by flowing water. The volume and velocity of flowing water determines the severity. Steep slopes may not require more than about 3 pounds per acre of **Slicky Sticky®**. Slight slopes with a high volume and high velocity of flowing water, running off from higher areas, may be impossible to control. It is not possible for Turfmaker Corp to guarantee the performance of any soil erosion product.

TURFMAKER CORP ROWLETT, TX 75088 SLICKYSTICKY.COM 972-463-2575 800-527-2304

SLICKY STICKY®

TURF MAKER CORP.
4931 GRISHAM
ROWLETT, TX 75088

PRECAUTIONARY MEASURES:

OSHA NON-HAZARDOUS

This product has been determined to be non-hazardous in accordance with OSHA 29CFR1910.1200. However, this product is intended for industrial use only, and should be handled in accordance with good industrial hygiene and safety practices. Avoid any unnecessary exposure. In the event of contact, wash with water.

CAUTION!

Spills of this material present a slip hazard when wet. Do not wet. Sweep up spilled material promptly, while still dry. After cleanup, flush area with water

For Industrial Use Only.
Read MSDS prior to using product.

In case of emergency
call: (972) 463-2575

HEALTH	0
FLAMABILITY	1
REACTIVITY	0

Package No.: 1
Lot # Q0295SOV

Made in USA

Component(s)
25085-02-3 COPOLYMER OF ACRYLAMIDE SODIUM ACRYLATE
7732-18-5 WATER
57-13-6 UREA

Gross Wt.: 17 Lbs / 7.5 Kgs
Net Wt. : 15 Lbs / 7 Kgs