

# MSDS Material Safety Data Sheet

**PROFILE Products, LLC**



CONWED1000®with Slik Shot

MSDS Number: CON045

Revision Date: 1/14/09

Page 1 of 4

## 1 PRODUCT AND COMPANY IDENTIFICATION

### Manufacturer

PROFILE Products, LLC  
750 LAKE COOK ROAD  
SUITE 440  
BUFFALO GROVE, IL 60089

### Contact:

Telephone Number: (847) 215-1144  
FAX Number: (847) 215-0577  
E-Mail: profileproducts.com  
Web www.profileproducts.com

**Product Name:** CONWED1000®with Slik Shot  
**Revision Date:** 1/14/09  
**MSDS Number:** CON045  
**CAS Number:** Not applicable  
**Product Use:** Erosion control mulch for hydraulic seeding

Product Description: Green dyed wood fibers with proprietary binder mixture

## 2 HAZARDS IDENTIFICATION

**Route of Entry:** Inhalation, skin contact, eye contact  
**Target Organs:**  
**Inhalation:** Wood dust may cause sneezing, irritation, and dryness of the nose and throat. Dust may aggravate pre-existing respiratory conditions.  
**Skin Contact:** Wood dust can cause irritation. Skin absorption is not known to occur.  
**Eye Contact:** Wood dust can irritate the eyes.  
**Ingestion:** No reports of human ingestion.

NFPA-ratings (scale 0-4): Health = 0, Fire = 2, Reactivity = 0

OSHA Classification: Wood dust is a hazardous substance as defined by the Hazard Communication Standard 29CFR 1910.1200

## 3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name
-----	-----	-----

## 4 FIRST AID MEASURES

<b>Inhalation:</b>	Usually not a problem. Remove to fresh air if respiratory irritation develops, and get medical aid promptly if irritation persists.
<b>Skin Contact:</b>	Usually not a problem. Wash off with running water if irritation is experienced.
<b>Eye Contact:</b>	Open eyelids and flush with water.
<b>Ingestion:</b>	Get medical attention.

## 5 FIRE FIGHTING MEASURES

<b>Flash Point:</b>	Not applicable
<b>Flash Point Method:</b>	Not applicable
<b>Autoignition Temperature:</b>	200-206°C (400-500°F)
<b>Flammability Classification:</b>	Combustible product

Conditions to avoid: In contact with flames or hot surfaces

Flammable- Extinguish with water; same as a wood fire

## 6 ACCIDENTAL RELEASE MEASURES

Scoop up product. Wear goggles and respirator if dust is produced in unventilated areas. Wet product will be slippery.

## 7 HANDLING AND STORAGE

<b>Handling Precautions:</b>	Clean up areas where dust settles. Minimize blowdown or other practices that generate high airborne dust concentrations.
<b>Storage Requirements:</b>	Store in a cool, dry place. Keep away from sources of ignition.

## 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

<b>Engineering Controls:</b>	None required for outdoor mixing and application. Use dust collection system for indoor handling operations.
<b>Protective Equipment:</b>	Eye Protection: Wear goggles when emptying bags and during other operations where there is a risk of dust entering the eyes. Gloves: Leather, plastic or rubber gloves could be worn to minimize skin irritation. Respirators: When handling methods generate dust at concentrations that exceed occupational exposure limits, wear a NIOSH approved respirator. A fabric respirator or a facepiece respirator with dust cartridges will generally provide adequate protection. Footwear: The product is slippery when wet. Wear appropriate footwear.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance:</b>	Dyed, green wood fibers - Pine and mixed hardwoods	<b>Boiling Point:</b>	
<b>Physical State:</b>	Wood Fibers	<b>Freezing/Melting Pt.:</b>	
<b>Odor:</b>	Mild wood odor	<b>Solubility:</b>	
<b>pH:</b>		<b>Spec Grav./Density:</b>	lighter than water
<b>Vapor Pressure:</b>	N/A		
<b>Vapor Density:</b>			

## 10 STABILITY AND REACTIVITY

<b>Stability:</b>	Stable product
<b>Conditions to avoid:</b>	Contact with strong acids and oxidizers may generate heat. Product may ignite at temperatures in excess of 200°C (400°F).
<b>Materials to avoid (incompatibility):</b>	Strong acids and oxidizers
<b>Hazardous Decomposition products:</b>	
<b>Hazardous Polymerization:</b>	Will not occur.

## 11 TOXICOLOGICAL INFORMATION

### EFFECTS OF CHRONIC EXPOSURE:

Inhalation: Frequent and repeated exposure to wood dust is associated with an increased risk of developing nasal cancer.  
Skin Contact: Although rare, wood dust may cause dermatitis in sensitized people.

### Occupational Exposure Limits:

Wood dusts- All other species: ACGIH (2007): TLV-TWA 1 mg/m<sup>3</sup> (Inhalable fraction); A4

Particulates Not Otherwise Regulated (PNOR): OSHA: PEL-TWA 15 mg/m<sup>3</sup> (Total Dust); 5 mg/m<sup>3</sup> (Respirable fraction)

Irritancy: Wood dust is a mild irritant  
Sensitization: Some wood dusts may cause allergic skin reactions

## 12 ECOLOGICAL INFORMATION



## 13 DISPOSAL CONSIDERATIONS

Normally can be disposed of as a wood residue. Ensure disposal is in compliance with local, provincial (state), and federal regulations.

## 14 TRANSPORT INFORMATION

DOT Class: Not regulated #

## 15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

-----

### REGULATORY KEY DESCRIPTIONS

-----

MASS = MA Massachusetts Hazardous Substances List  
NRC = Nationally Recognized Carcinogens  
OSHA WAC = OSHA Workplace Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
TXAIR = TX Air Contaminants with Health Effects Screening Level

CERCLA = Superfund clean up substance  
CSWS = Clean water Act Hazardous substances  
EHS302 = Extremely Hazardous Substance  
EPCRAWPC = EPCRA Water Priority Chemicals  
HAP = Hazardous Air Pollutants  
NJHS = NJ Extraordinarily Hazardous Substances  
NJHS = NJ Right-to-Know Hazardous Substances  
OSHA PSM = OSHA Chemicals Requiring process safety management  
SARA313 = SARA 313 Title III Toxic Chemicals

## 16 OTHER INFORMATION